Index

A

Addition operator (+), 1–4
Addressing, 1–5
Address space
  changing, 2–1
  display of, 1–6
  toggling between, 2–9
_ADROFF, 1–3, 3–2
  example, 3–8
_ADR qualifier for ;T, 2–3
  example, 3–8
AND logical operator (&), 1–4
ASCII byte mode examine ('), 2–6, 3–14
  example, 3–18
ASCII byte prefix (_'), 1–2
  example, 3–21
ASCII characters
  entering, 3–21
ASCII word mode examine ("), 2–6, 3–14
  example, 3–18
ASCII word prefix (_"), 1–2
  example, 3–21
At-sign (@)
  See Examine indirect

B

Backslash (\ )
  See Byte mode examine
;B command
  description, 2–5
  example, 3–12
_BIN qualifier for ;R, 2–2, 3–7
BPT instruction
  patch with SIPP, 3–2
Breakpoints
  displaying, 2–5
  example, 3–23
  proceeding after, 2–5, 3–14
  setting, displaying, removing
    example, 3–12
  setting and removing, 2–5
Breakpoints (Cont.)
  single-step, 2–6, 3–14
  with fully-mapped monitors, 5–2
Byte mode examine (\ ), 2–7, 3–14
  example, 3–18

C

Changing locations, 2–7
  example, 3–19
Circumflex (^)
  See Examine previous
Closing locations
  example, 3–14
Colon (:)
  See Defining user symbols
Commands, 2–1
Command summary, C–1
CTRL/C, 2–9
CTRL/Q, 2–9
CTRL/S, 2–9
CTRL/U, 2–10
CTRL/W, 2–10
Current location symbol (.), 3–22

D

_DATOFF, 1–3, 3–2
  example, 3–9
DBGDEM example program
  linking for fully-mapped monitors, 5–2
  listing of, A–1
  running under mapped monitors, 3–5
  with mapped monitors, 5–1
DBGSYM.SAV, 1–1, 3–1, 3–2, 4–1
  procedure, 4–1
;D command
  description, 2–5
  example, 3–13
_DEC qualifier for ;R, 2–2, 3–7
Defining user symbols (:), 2–4
  example, 3–11
Deleting user symbols, 2–5, 4–1

Device handler debugging, 5–1
Display values (=), 2–9
Distribution
  RT–11, 3–1
  RTEM, 3–2
Division operator (_/), 1–4
Dollar sign (_$)
  See Hexadecimal prefix
_D qualifier for ;M, 2–1

E

Equal sign (=)
  See Display values
Error messages, B–1
_ESC qualifier for ;T, 2–3
Examine
  indirect, 2–8
    I-space, 2–8
  locations, 2–6, 3–14
  next, 2–8
  previous, 2–8
  symbols, 2–9
Examine indirect
  D-space, 2–8
Execute program, 2–5, 3–14
  example, 3–23
Exit DBG–11 with 0;G, 2–5
Expressions, 1–4
  angle brackets for nesting, 1–5
  display values, 2–9
  valid elements, 1–4

F

Features, 1–1
Fully-mapped monitors
  DBGDEM with, 5–1

G

;G command, 3–14
  description, 2–5
Grave accent (‘)
  See Address space
GRH option identifier, 3–5

H

HARD option identifier, 3–5
Hexadecimal prefix (_$), 1–2, 3–21
Hexadecimal prefix (_$) (Cont.)
  example, 3–21
Hexadecimal values
  entering, 3–21
_HEX qualifier for ;R, 2–2, 3–7

I

IO: message, 2–4
IOT instruction traps, 2–4
_I qualifier for ;M, 2–1

K

;K command
  description, 2–5, 4–1
  example, 3–11
_K qualifier for ;M, 2–2
_K qualifier for ;T, 2–3

L

Last displayed value symbol Q, 3–22
Left bracket ([)
  See Symbolic data mode examine
Linefeed examines next location, 2–8
Location, current
  equating symbol for, 1–3

M

MACRO–11 instructions
  entering, 3–19
Mapped monitors
  DBGDEM with, 5–1
;M command
  description, 2–1
  using, 5–2
MMR3, 2–1
monitors
  different displays under, 3–6
Multiplication operator (*), 1–4

N

_NOADR qualifier for ;T, 2–3
_NOESC qualifier for ;T, 2–3
_NOK qualifier for ;T, 2–3
_NOREG qualifier for ;T, 2–3
_NORUB qualifier for ;T, 2–3
  example, 3–7
_NOS qualifier for ;T, 2–3

_NOSYM qualifier for ;T, 2–3
_NOU qualifier for ;T, 2–3
Numeric data mode examine (|), 2–7, 3–14
  example, 3–17
Numeric values, 1–2
  entering, 1–2, 3–19

O

_OCT qualifier for ;R, 2–2, 3–7
Opening locations
  example, 3–14
Open locations, 2–6
Operators
  addition, 1–4
  division, 1–4
  logical AND, 1–4
  logical OR, 1–4
  multiplication, 1–4
  subtraction, 1–4
  unary, 1–5
OR logical operator (!), 1–4
Output radix, 1–2
  setting, 2–2
Overview, 1–1

P

PARs
  modifying, 5–3
;P command, 3–14
  description, 2–5
Percent sign (%)
  See Radix–50 mode examine
Percent sign (_%)
  See Radix–50 prefix
Period (.)
  See Current location symbol
Pound sign (#)
  See Examine indirect
Processor mode
  changing, 2–1, 2–2
  display of, 1–6
  rotating between, 2–8
PRO option identifier, 3–5

Q

Q, last displayed value symbol, 3–22
Quotation mark (")
  See ASCII word mode examine
Quotation mark (')
  See ASCII byte mode examine
Quotation mark (_")
  See ASCII word prefix
Quotation mark (_')
  See ASCII byte prefix

R

Radix–50 mode examine (%), 2–7, 3–14
  example, 3–18
Radix–50 prefix (_%), 1–2
  example, 3–21
Radix–50 values
  entering, 3–21
  use of underscore (_) for space, 3–21
Radix control, 3–7
Radix for output, 1–2
Radix setting, 2–2
;R command
  description, 2–2
  example, 3–7
Register display, 2–3
  effect of ;R command, 2–2
  example, 3–10
Registers, 1–3
  DBG–11 internal, 1–3
  machine, 1–3
_REG qualifier for ;T, 2–3
RT–11
  distribution, 3–1
  starting DBG–11, 3–2
RT11Zx monitors, 5–1
RTEM
  distribution, 3–2
Rubout character, 2–9
Rubouts, 2–3
  example, 3–7
_RUB qualifier for ;T, 2–3
  example, 3–7

S

;S command, 3–14
  description, 2–6
SD: option identifier, 3–5
SDH.SYS, 1–1, 3–1, 5–1
SDHX.SYS, 1–1, 3–2, 5–1
SDM.SYS, 1–1, 3–2
SDS.SYS, 1–1, 3–1

SDSX.SYS, 1–1, 3–1
SET commands, 3–3
  SD ADROFF=val, 3–3, 3–9
  SD BREAK, 3–3, 5–1
  SD CSR=val, 3–3
  SD DATOFF=val, 3–4, 3–10
  SD PC, 3–4
  SD PS, 3–4
  SD SYSGEN, 3–2, 3–4
  SD [NO]ESC, 3–4
  SD [NO]K, 3–4
  SD [NO]REG, 3–4, 3–10
  SD [NO]S, 3–4
  SD [NO]U, 3–5
  ST SYSGEN, 4–1
Single-step, 2–6, 3–14
SIPP to set BPT, 3–2
Slash (/)
  See Symbolic instruction mode examine
SOFT option identifier, 3–5
Special characters, 2–9
_S qualifier for ;M, 2–2
_S qualifier for ;T, 2–3
ST.SYS, 4–1
Start program, 2–5
.STB files, 4–1
STM.SYS, 4–1
STX.SYS, 4–1
Subtraction operator (-), 1–4
Symbolic data mode examine ([ ), 2–7, 3–14
  example, 3–16
Symbolic instruction mode examine (/), 2–7, 3–14
  example, 3–16
Symbols, 1–3
  current displayed location and value, 1–3
  DBG–11 internal, 1–3
  DBG–11 permanent, 1–3
  display values, 2–9
  machine register, 1–3
  user-defined, 1–4
  valid character set, 1–4
_SYM qualifier for ;T, 2–3
  example, 3–9

T

T10: message, 2–4, 3–25
_T10 qualifier for ;V, 2–4
T4: message, 2–4
_T4 qualifier for ;V, 2–4
;T command
  Defaults, 2–3
  description, 2–2
  example
    _ADR/_NOADR, 3–8
    _REG/_NOREG, 3–10
    rubouts, 3–7
    _SYM/_NOSYM, 3–9
Tilde (~)
  See Processor mode
TR: message, 2–4
Trap handling, 2–3, 3–25
TRAP instruction traps, 2–4
.TRPSET directive and ;V command, 2–4

U

(U) for user mode mapping, 3–1
Unary operators, 1–5
_U qualifier for ;M, 2–2
_U qualifier for ;T, 2–3
User symbols
  defining, 2–4
    example, 3–11, 3–23
  deleting, 2–5
    example, 3–11
  examining, 3–12

V

Value, current
  equating symbol for, 1–3
;V command
  description, 2–3
Vertical bar (|)
  See Numeric data mode examine
Video display
  See Register display

X

XOFF, 2–9
XON, 2–9