Index

A

Aborting commands, 2–10
Aborting program execution, 2–11
ABORT keyboard command
  using, 7–12
Absolute addresses, 20–3
/ALL option
  RECALL command, 10–13
Answer file
  editing to change command support, 13–9
/ASCII
  with TRANSF.EXE, 12–12
  with TRANSF.TSK, 12–14
ASCII file transfers
  with TRANSF.EXE, 12–13
  with TRANSF.SAV, 12–17
  with TRANSF.TSK, 12–15
Assembler
  MACRO, 19–4
  support for, 1–8
ASSIGN keyboard command
  changing the output device, 5–4

B

.BAC file type, 18–11
Background environment
  under mapped monitors, 6–3
Background job
  creating an example, 5–2
  directing input to, 5–3
  editing an example, 5–2
  running an example, 5–2
  terminating, 5–5
Background program
  See Background job
Backing up data, 14–1
  reasons for, 14–1
  to diskettes, 14–5
  to disks, 14–12
  to logical disks, 14–14
  to magtapes, 14–18
Backing up files
  directory of, 3–13
  explanation of, 3–12
  restoring, 3–14
Backup directories
  disk, 14–13
  diskette, 14–8
  logical disk, 14–16
  magtape, 14–20
BACKUP keyboard command
  using, 3–11
  with data backup operations, 14–4
  with diskettes, 14–5
  with disks, 14–12
  with file-structured data, 14–3
  with logical disks, 14–14
  with magtapes, 14–18
  with non-file-structured data, 14–3
Backup operations
  to diskettes, 14–5
    all file images, 14–7
    device image, 14–6
    directory operations, 14–8
    maintaining directories, 14–8
    selected file images, 14–7
    wildcards, 14–8
    with BACKUP command, 14–5
    with COPY command, 14–10
    with COPY/DEVICE command, 14–12
  to disks
    BACKUP to savesets, 14–12
    directory operations, 14–13
    restoration operations, 14–14
    wildcards, 14–13
    with BACKUP command, 14–12
    with COPY command, 14–16
    with COPY/DEVICE command, 14–18
  to logical disks, 14–14
    directory operations, 14–16
    restoration operations, 14–16
    with BACKUP command, 14–14
  to magtapes, 14–18

Backup operations
to magtapes (Cont.)
creating savesets, 14–19
directory operations, 14–20
initializing, 14–19
restoration operations, 14–21
wildcards, 14–19
with BACKUP command, 14–18
with COPY/DEVICE command, 14–23
Base address
modifying VM, 11–9
BASIC
See BASIC-PLUS
BASIC.ERR, 18–1
BASIC.SAV, 16–4
BASIC-PLUS
COMPILE command, 18–10
debugging programs, 22–2
DELETE command, 18–6
EXIT command, 18–11
immediate mode, 18–3
intermediate translated program, 18–10
LIST command, 18–4
LISTNH command, 18–5
NEW command, 18–4
OLD command, 18–7
PRINT command, 18–3
program development, 18–1, 18–4
using KED, 18–10
REPLACE command, 18–10
RUNNH command, 18–8
running the program, 18–7
SAVE command, 18–10
SCRATCH command, 18–6
stopping interpreter, 18–11
support for, 16–3
under mapped monitors, 18–2
using, 18–1
BATCH
compared with indirect command files, 15–1
/BINARY
with TRANSF.EXE, 12–12
with TRANSF.TSK, 12–14
Binary code, 19–10
decimal and octal equivalents, 19–11
BINARY file transfers
with TRANSF.EXE, 12–13
with TRANSF.SAV, 12–17
with TRANSF.TSK, 12–16
Bit (PDP–11) explained, 19–10
Booting the computer, described, 2–5
Bugs
See Programming errors
BUP
system memory requirements, 14–2
Byte (PDP–11) explained, 19–10

C

C
support for, 16–3
CCL
compared with DCL, CSI, 2–8
CF:
assigning to VM device, 11–11
CLOSELOG command, example, 12–18
Combining files, 3–4
Command conditionals, 13–8
Command format, DCL, 2–32
Command line editing
See also Single-line command editor
basic demonstration, 10–6
keypad, 10–7
keypad demonstration, 10–8
turning on, 10–2
Command lines
editing, 10–3
Command options, described, 2–12
Command processing, described, 2–8
Commands
basic editing of, 10–4
defining new, 13–1
keypad editing of, 10–7
recalling previously stored, 10–10
redefining, 13–8
redefining existing, 13–1
removing support for distributed, 13–8
storing, 10–10
Command syntax described, 2–7
Communications
connecting with host, 12–8
establishing, 12–7
logging, 12–9
transferring files, 12–11
using, 12–8
Communications components, 12–2
configuring the, 12–4
host computer, 12–3
local computer, 12–2

Communications components (Cont.)
port controllers, 12–3
RT–11 monitors, 12–5
transmission medium, 12–4
Communications port controllers, 12–3
addressing, 12–4
baud rate, 12–4
local computer, 12–5
with local computer, 12–6
with transmission medium, 12–6
Compilers
FORTRAN, 17–1
setting default FORTRAN type, 17–1
support for, 1–8
using FORTRAN, 17–2
CONFIG
determining support for ZM monitor with, 6–2
COPY/DEVICE keyboard command
backups to diskettes, 14–12
backups to disks, 14–18
backups to magtapes, 14–23
with data backup operations, 14–5
COPY keyboard command
backups to diskettes, 14–10
backups to disks, 14–16
using, 3–4
with data backup operations, 14–4
with file-structured data, 14–3
CPU, 1–1
CREATE keyboard command
with logical disks, 9–2
CREF.SAV, 16–4
CREF listing
See Cross-reference (CREF) listing
CSI
compared with DCL, CCL, 2–8
CTRL/B, 5–3
with SL, 10–5
CTRL/C, 2–41, 7–12
in indirect command files, 15–3
CTRL/C CTRL/C, 2–42
at DCL level, 2–11
CTRL/D
with SL, 10–5
CTRL/E
with SL, 10–5
CTRL/F, 5–3
with SL, 10–5
CTRL/H
CTRL/H (Cont.)
with SL, 10–5
CTRL/J
with SL, 10–5
CTRL/O, 2–42
CTRL/R
with SL, 10–5
CTRL/U, 2–42
with SL, 10–6
CTRL/V
with SL, 10–5
CTRL/W, 7–8
with SL, 10–5
CTRL/X, 7–6

D

Data backup
See Backing up data
Date
See also Time
displaying, 2–13
entering, 2–13
DBG-11, 22–3
example debugging procedure with, 22–7
requires BPT instruction, 22–5
running, 22–7
DBG-11 handler
See SD handler
DCL
aborting a command, 2–10
command format, 2–32
command prompts, 2–34
compared with CCL, CSI, 2–8
introduction to, 2–8
issuing a command, 2–9
options, 2–12
redefining commands, 13–8
relationship to keyboard commands, 2–7
ddn, 2–18
Debugger, symbolic
See DBG-11
Debugging
BASIC-PLUS programs, 22–2
example MACRO program showing, 22–7
FORTRAN programs, 22–3
MACRO programs, 22–3
DELETE keyboard command
using, 3–9
DEMOB1.BAS, 18–6

DEMOFG.MAC
running, 5–2, 5–4
DEMOM1.MAC, 19–1
Device handler files
naming convention, 2–22
Device handlers, 2–21
Communications, 12–5
configuring from start-up files, 8–2
file names for, 2–21
intro to, 1–7
must load for system jobs, 7–2
naming convention, 2–21, 2–22
Device names, 2–22
format for, 2–18
physical, 2–18
Devices
if media, See also Volumes
backing up to diskettes, 14–6
configuring from start-up files, 8–2
data backup, 14–5
increasing number of directory segments for, 9–2
naming convention, 2–22
DIBOL
support for, 16–3
DIFFERENCES keyboard command
using, 3–5
Digital command language
See DCL
DIRECTORY keyboard command
with unmounted logical disks, 14–17
Directory listings, 2–15
Directory operations
disk backup volumes, 14–13
diskette backup volumes, 14–8
logical disk backup volumes, 14–16
magtape backup volumes, 14–20
Diskettes
as backup media, 14–5
Disks
as backup media, 14–12
DISMOUNT keyboard command
with logical disks, 9–4
DK
defined, 2–23
device, 8–3
.DSK file type
indicates logical disk, 9–2

E

-E-, 2–11
Editing text files, 4–7
Error messages, 2–11
format explained, 2–11
levels of, 2–11
EXECUTE keyboard command
with FORTRAN, 17–15
with MACRO, 19–19
Extended memory, 6–2
VM device in, 11–3

F

-F-, 2–11
F77.SAV, 16–4
F77COM.MSG, 16–4, 17–3
F77OTS.OBJ, 16–4, 17–3
combined with SYSLIB?, 17–13
F77XM.SAV, 16–4
Factoring file specifications, 2–31
FAST command, example, 12–19
Fatal messages, 2–11
FB monitor, 5–3
BUP memory requirements, 14–2
configuring VM device for, 11–2
FDT, 22–3
Files
See also Text file
backing up, 3–11
backing up to diskettes, 14–7
backing up to disks, 14–13
combining, 3–4
commands used in managing, 3–20
comparing ASCII, 3–5
copying, 3–3
deleting, 3–9
displaying contents of, 3–2
factoring file specifications, 2–31
listing directories of, 2–15
logging, 12–9
logically grouping, 9–1
name defined, 2–29
on volumes, 2–2
printing, 3–2
protecting, 2–2, 3–10
backing up, 2–2
hardware protection for, 2–2
PROTECT command, 2–3
write-protecting, 2–2

Files (Cont.)
renaming, 3–8
restoring from backup, 3–14
specifying, 2–29
squeezing on volume, 3–16
stopping the printing, 3–3
transferring, 12–11
type defined, 2–29
unprotecting, 3–10
wildcards with, 2–30
Filespec, 2–29
File specifications, 2–29
factoring, 2–31
File-structured data
backing up, 14–3
File transfers
See also Communications
without TRANSF on host, 12–17
with TRANSF on host, 12–11
Foreground/background
communications, 5–3
Foreground/background environment, 5–1
Foreground/background monitor
See FB monitor
Foreground environment
under mapped monitors, 6–4
Foreground job
creating an example, 5–4
directing input to, 5–3
executing an example, 5–4
linking an example, 5–4
loading device handlers, 5–4
terminating, 5–5
unloading, 5–6
/FOREGROUND option
LINK keyboard command, 5–4
Foreground program
See Foreground job
FORLIB.OBJ, 16–4, 17–3
combined with SYSLIB?, 17–13
FORTRA.SAV, 16–4
/FORTRAN
See also FORTRAN–77
See also FORTRAN IV
compiling source program, 17–5
debugging programs, 22–3
FDT debugger, 22–3
linking object modules, 17–11
running save image, 17–13
/FORTRAN (Cont.)
setting default compiler, 17–1
using compiler, 17–2
using libraries, 17–2
with TRANSF.EXE, 12–12
with TRANSF.TSK, 12–14
FORTRAN–77
See also FORTRAN
compilation listing, 17–9
described, 17–1
linking object modules, 17–13
load map for, 20–10
support for, 16–3
FORTRAN file transfers
with TRANSF.EXE, 12–13
with TRANSF.SAV, 12–17
with TRANSF.TSK, 12–16
FORTRAN IV
See also FORTRAN
compilation listing, 17–6
described, 17–1
linking object modules, 17–13
load map for, 20–8
support for, 16–3
FRUN keyboard command, 5–4

G

GOLD key, 4–4
with SL, 10–4

H

Hard boot, described, 2–6
Hardware, 1–1
backup, 1–3
keyboard, 2–3
memory, 1–1
processor, 1–1
storage devices, 1–2
terminal, 1–2
Hardwired serial line connections, 12–4
HELP
display explanation, 2–36
using, 2–35
with KED, 4–3
with SL, 10–4
with TRANSF.EXE, 12–12
with TRANSF.TSK, 12–15
High-level languages, 16–1
compared to machine-level, 16–2

Host computer, 12–3
facilities available, 12–8
logging, 12–9

I

-I-, 2–11
/IMAGE
with TRANSF.EXE, 12–12
with TRANSF.TSK, 12–15
IMAGE mode file transfers
with TRANSF.EXE, 12–13
IMAGE mode transfers
with TRANSF.SAV, 12–17
with TRANSF.TSK, 12–16
Immediate mode, 18–3
IND
compared with indirect command files, 15–1
running from UCL, 13–6
INDEX
using, 2–39
Indirect command files
compared with BATCH, 15–1
compared with IND, 15–1
creating, 15–2
creating (example), 7–4
limitations of, 15–2
nesting within each other, 15–5
running, 15–4
running from UCL, 13–5
using, 15–1
when large, 15–3
with UCL, 13–5
Indirect control files
with UCL, 13–6
Indirect files
See Indirect command files
Information messages, 2–11
INITIALIZE keyboard command
with logical disks, 9–3
INSERT mode
single-line command editor, 10–4
Inspecting text files, 4–5
Installation
on VM device, 11–1
Interpreters
support for, 1–8
using BASIC-PLUS, 18–1
Issuing commands, DCL, 2–9

J

Jobs
background, 5–2
foreground, 5–4
system introduced, 6–4

K

KED
creating text file, 4–3
editing file, 4–7
entering text, 4–4
GOLD key, 4–4
HELP, 4–3
inspecting file, 4–5
introduction to, 4–1
journaling, 4–10
keypad legend, 4–3
figure of, 4–3
line wrap, 4–9
screen width, 4–10
SL set condition, 10–2
KED editor
See KED
KEX
virtual KED, for functionality See KED
as system job (example), 7–6
multiple editors example, 7–8
KEX editor
See KEX
Keyboard
described, 2–3
Keyboard commands, 2–7
See also DCL
Keyboard keys, 2–4
Keypad editor
See KED
Keypad keys
as used by KED, 4–3
figure of, 4–3
as used by SL, 10–7
KMON
SL set condition, 10–2

L

Language processors
support for, 1–7
LD
See Logical disks

LD handler
See also Logical disks
extended device-unit support, 9–2
LD utility
See logical disks
Library files, 21–2
building object, 21–4
creating, 21–2
macro, 21–1
object, 21–1
updating object, 21–5
used by assembler, 21–1
used by linker, 21–1
LIBRARY keyboard command
using, 21–4
LINK.SAV, 16–4
Linking object modules
FORTRAN, 17–11
MACRO, 19–16
LINK keyboard command
linking a foreground program, 5–4
using, 20–6
Link operations, 20–1
absolute program sections, 20–4
address assignment, 20–3
library references, 20–3
load map, 20–6
examining, 20–7
load module, 20–6
overlays, 20–6
overview of, 19–16
program relocation, 20–3
purposes of, 20–1
relocatable program sections, 20–4
symbolic references, 20–2
Link process
See Link operations
LOAD keyboard command, 5–4
Load maps, 20–6
examining, 20–7
Load module, 20–6
Local computer, 12–2
communications port controller, 12–6
starting VTCOM, 12–7
/LOG
with TRANSF.EXE, 12–12
with TRANSF.TSK, 12–15
Logging data, 12–18
Logging files, 12–9
Logical device names, 2–23
assigning, 2–24
Logical disks
as backup volumes, 14–14
associating with unit number, 9–3
changing unit number, 9–4
creating, 9–2
default file type .DSK, 9–2
determining status of, 9–4
determining the file name of, 9–2
directories of unmounted, 14–17
directory structure, 9–3
initializing, 9–3
introduction to, 2–26
making larger, 9–8
mounting, 9–3
naming the unit, 9–3
nesting within each other, 9–4
procedure for creating, 9–6
procedure for nesting, 9–5
recursion rule explained, 9–4
size restrictions, 9–4
unit numbers explained, 9–4
using (exercise for), 9–6
Logical disk subsetting utility
See Logical disks
Low memory, 6–2
LP, 3–2
LS, 3–2

M

Machine-level languages, 16–1
compared to high-level, 16–2
MACRO.SAV, 16–4
MACRO–11
support for, 16–3
MACRO assembler
assembling source programs, 19–6
creating a program, 19–3
CREF listing, 19–13
DBG-11 debugger, 22–3
debugging programs, 22–3
linking object modules, 19–16
listing, 19–5, 19–7
cross-reference listing, 19–6
symbol table, 19–12
listing explanation, 19–9
binary code, 19–10
error examination, 19–14

MACRO assembler
listing explanation (Cont.)
octal numbers, 19–9
relative locations, 19–9
storage locations, 19–9
load map for, 20–7
ODT debugger, 22–3
running a program, 19–18
symbol table, 19–12
using the assembler, 19–4
Macro libraries, 21–1
See also Library
Magtapes
as backup volumes, 14–18
COPY/DEVICE command, 14–23
initializing as backup volumes, 14–19
transporting backed-up to VMS, 14–22
Mapped monitors
advantages of, 6–2
background environment under, 6–3
BUP memory requirements, 14–2
configuring VM device for, 11–3
editing start-up command file for, 8–3
foreground environment under, 6–4
making system monitor, 6–3
requirements for using, 6–1
running programs under, 6–3
running VM device under, 11–3
system job environment under, 6–4
Mass storage volumes, 2–1
Media backup
See Backing up data
Messages
error, 2–11
fatal, 2–11
information, 2–11
unconditional, 2–11
warning, 2–11
Modem connections, 12–4
Monitors
intro to, 1–5
MOUNT keyboard command
with logical disks, 9–3

O

Object libraries, 21–1
See also Library
Object module relocation, 20–4
ODT, 22–3
OFF
SL set condition, 10–2
ON
SL set condition, 10–2
On-line HELP utility
See HELP
On-line INDEX utility
See INDEX
OPENLOG command, example, 12–18
Output device
changing, 5–4
Overlay segments
overview of, 20–6

P

Parallel-interface printers (LP), 3–2
PASCAL
support for, 16–3
Printers
determining interface type, 3–2
PRINT keyboard command
using, 3–3
Processor
increasing speed of, 11–2
Programming errors
avoiding, 22–1
clerical, 22–2
logic, 22–2
syntax, 22–2
Programming errors, correcting
See Debugging
Programming languages
choosing, 16–1, 16–3
required files, 16–4
Program sections, 20–4
/PROGRESS
with TRANSF.EXE, 12–12
with TRANSF.TSK, 12–15
/PROMPT
with TRANSF.EXE, 12–12
with TRANSF.TSK, 12–15
Protecting files, 2–3, 3–10
PROTECT keyboard command
using, 3–10

R

Rebooting the computer, described, 2–6
RECALL

RECALL (Cont.)
SL set condition, 10–2
RECALL command, 10–2
with UCF support, 13–11
Relative addresses, 20–3
Removable disks
See Disks
RENAME keyboard command
using, 3–8
REPLACE mode
single-line command editor, 10–4
Resident handler, 7–2
Restoration operations
from diskettes, 14–10
from disks
complete savesets, 14–14
selected files, 14–14
wildcards, 14–14
from logical disks
files, 14–16
unmounted, 14–16
wildcards, 14–16
from magtapes
device image saveset, 14–21
file images before V5.5, 14–22
files on device saveset, 14–22
wildcards, 14–22
Restoring data
See Restoration operations
Restoring savesets
See Restoration operations
RSX–11 host
transferring files with a, 12–14
RT–11 computer system
description of, 1–1
RT–11 host
file transfers with a, 12–16
RT–11 operating system
application programs, 1–9
basic concepts of, 2–1
command syntax described, 2–7
configuring, 8–1
documentation for, 1–9
restarting, 2–6
software components, 1–4
starting, 2–5
RUN keyboard command
background job, 5–2

S

Savesets
See also Backup operations
See also Directory operations
See also Restoration operations
defined, 14–12
with diskette media, 14–8
with magtape media, 14–19
with removable disks, 14–12
SB monitor
BUP memory requirements, 14–2
SDH.SYS, 22–4
SD handler
installing, 22–4
loading, 22–7
SDHX.SYS, 22–4
Serial-interface printers (LS), 3–2
SET ERROR condition
with indirect command files, 15–5
SET FORTRA F4, 17–2
SET FORTRA F77, 17–2
SET keyboard commands
SET ERROR condition
with indirect command files, 15–5
SET FORTRA F4, 17–2
SET FORTRA F77, 17–2
SET KMON IND
with indirect command files, 15–4
SET KMON KMON
with indirect command files, 15–4
SET LD CLEAN
with logical disks, 9–6
SET SL KED, 10–2
SET SL KMON, 10–2
SET SL OFF, 10–2
SET SL ON, 10–2
SET SL RECALL, 10–2
SET SL SYSGEN, 10–3
SET SL VT102, 10–3
SET VM BASE=nnnnnn
with VM device, 11–9
SET VM SIZE=0
with VM device, 11–9
SET KMON IND
with indirect command files, 15–4
with UCL, 13–6
SET KMON KMON
with indirect command files, 15–4
SET LD CLEAN

SET LD CLEAN (Cont.)
with logical disks, 9–6
SET SCREEN
using, 4–10
SETUP
described, 2–14
SET VM BASE=nnnnnn
with VM device, 11–9
SET VM SIZE=0
with VM device, 11–9
SET WRAP
using, 4–9
SHOW COMMANDS
with UCL, 13–5
SHOW CONFIGURATION
using, 6–1
SHOW keyboard commands
SHOW COMMANDS
with UCL, 13–5
SHOW CONFIGURATION, using, 6–1
SHOW SUBSET
with logical disks, 9–4
SHOW SUBSET keyboard command
with logical disks, 9–4
Single-line command editor
See also SLMIN
basic functions, 10–4
command line editing, 10–3
basic editing demonstration, 10–6
keypad, 10–7
keypad demonstration, 10–8
nonkeypad, 10–4
functions
basic, 10–4
keypad, 10–7
recalling commands, 10–10
saving a command, 10–14
storing commands, 10–10
GOLD key, 10–4
HELP function, 10–4
if conflicting sysgen options, 10–3
INSERT mode, 10–4
keypad keys, 10–7
RECALL command, 10–2
recalling command functions
arrow keys, 10–11
changing cycling, 10–12
cycling method, 10–11
distributed cycling, 10–12
keypad, 10–11
Single-line command editor
recalling command functions (Cont.)
RECALL command, 10–13
recalling commands, 10–10
REPLACE mode, 10–4
saving a command, 10–14
storing commands, 10–10
turning on, 10–2, 10–3
with start-up command file, 8–5
SJ monitor
configuring VM device for, 11–2
SL
See Single-line command editor
SLMIN
minimal SL editor, 10–14
only with unmapped monitors, 10–14
using, 10–15
SLOW command, using, 12–19
Soft boot, described, 2–6
Software
operating system, 1–3
SPOOL
from start-up command file, 8–6
with TRANSF.EXE, 12–13
SQUEEZE keyboard command
using, 3–16
SRUN keyboard command
using, 7–5
Start-up indirect command files
editing procedure, 8–3
running, 8–8
using, 8–1
/STATISTICS
with TRANSF.EXE, 12–13
with TRANSF.TSK, 12–15
Storage medium
See storage devices
/SUBSET option
BACKUP keyboard command, 14–14
SY
defined, 2–23
device, 8–3
Symbols
global, 20–2
internal, 20–2
Symbol table, 19–12
Syntax, command described, 2–7
SYSGEN
SL set conditon, 10–3

SYSLIB.OBJ, 16–4, 17–3, 21–1
SYSMAC.SML, 16–4, 21–1
System device
  VM as, 11–4
System generation
  from VM device, 11–12
  removing command support, 13–2
  using command conditions, 13–8
  with UCL, 13–8
System job environment
  under mapped monitors, 6–4
System jobs
  aborting, 7–11
    from indirect files, 7–13
  before starting, 7–1
  calling, 7–6
    from another system job, 7–7
    from background, 7–7
  CTRL/X with, 7–6
  interaction between (example of), 7–8
  naming, 7–6
  order of loading, 7–2
  starting, 7–2
    from command line, 7–5
    from indirect command file, 7–3
    from start-up command file, 7–3
  unloading, 7–12
    from indirect files, 7–13
  using, 7–1
System software
  defined, 1–3

T

/TERMINAL
  with TRANSF.EXE, 12–12
  with TRANSF.TSK, 12–14
Terminal keyboard
  See Keyboard
Text file
  creating, 4–3
  editing existing, 4–7
  inspecting existing, 4–5
Text files
  comparing, 3–5
Time
  displaying, 2–14
  entering, 2–13
/T option
  with TRANSF.SAV, 12–17
TRANSF
  host computer, 12–3
TRANSF.EXE, 12–5
  ASCII transfers, 12–13
  BINARY transfers, 12–13
  FORTRAN-formatted transfers, 12–13
  IMAGE transfers, 12–13
  using, 12–11
TRANSF.SAV, 12–5
  using, 12–16
TRANSF.TSK, 12–5
  ASCII transfers, 12–15
  BINARY transfers, 12–16
  FORTRAN-formatted transfers, 12–16
  IMAGE transfers, 12–16
  using, 12–14
Transferring files, 12–11
Transmission medium, 12–4
  communications port controller, 12–6
  configuring, 12–7
  hardwired, 12–4
  modem, 12–4
TYPE keyboard command
  using, 3–2

U

-U-, 2–11
UCF, 13–1
  changing data file, 13–16
  changing error message name, 13–15
  compared to UCL, 13–1, 13–11
  creating, 13–11, 13–14
  data file considerations, 13–14
  from UCL, 13–11
  from VM, 13–16
  imposes system overhead, 13–3
  optimizing, 13–15
  reasons for using, 13–3
  RECALL command restricted, 13–11
  turning on, 13–14
  with existing commands, 13–3
UCL, 13–1
  adding command line information, 13–4
  changing data file, 13–7
  changing UCL commands, 13–5
  command syntax, 13–3
  compared to UCF, 13–1
  creates UCF, 13–11
  displaying command definitions, 13–5

UCL (Cont.)
new commands only, 13–2
optimizing, 13–7
preferred over UCF, 13–2
redefine with system generation, 13–2
running indirect control files from, 13–6
running indirect files from, 13–5
Unconditional messages, 2–11
UNLOAD keyboard command, 5–6
Unprotecting files, 3–10
UNPROTECT keyboard command
using, 3–10
User command linkage
See UCL
User commands first
See UCF
Utility programs, 2–37
intro to, 1–7
location when running, 2–39
running from start-up files, 8–2

V

VAX processors
can read backed-up magtape volumes, 14–22
Virtual memory device
See VM device
VM device
See also VM handler
ASSIGN device DK, 11–7
ASSIGN DK SFD, 11–7
as system device, 11–1
base address for
determining, 11–11
lowering, 11–4
modifying, 11–9
blocks needed for, 11–10
booting, 11–9
comparison with hard disk system device, 11–10
configuring for all of extended memory, 11–2
configuring for FB monitor, 11–2
configuring for mapped monitors, 11–3
configuring for SBmonitor, 11–2
creating working system, 11–5
initial start-up file, 11–6
required indirect command file, 11–8
VM start-up file, 11–6
VM device (Cont.)
if command file aborts, 11–9
initializing and copying system files to, 11–8
LOAD system job handlers, 11–7
manditory system files, 11–8
memory considerations, 11–11
modifying size, 11–9
multiple working systems, 11–10
optional files for, 11–5
required files for creating, 11–4
requirements for using, 11–1
running RT–11 from, 11–9
running your programs from, 11–14
SPOOL work file with, 11–7
uses volatile memory, 11–2
when can't use free blocks, 11–7
working model system for, 11–5
working system (minimal), 11–14
working system for MACRO–11 programmer, 11–11
working system for performing SYSGEN, 11–12
VM handler
See also VM device
VMS host
transferring files with a, 12–11
Volumes
backing up to diskettes, 14–6
backing up to disks, 14–13
backing up to magtapes, 14–19
squeezing, 3–16
when fragmented, 3–16
VT102
SL set condition, 10–3
VTCOM
as background job, 12–8
as foreground job, 12–7, 12–8
as system job, 12–7, 12–8
CLOSELOG command, using, 12–18
FAST command, using, 12–19
from start-up command file, 8–5
local computer, 12–2
OPENLOG command, using, 12–18
SEND command, using, 12–17
SLOW command
using, 12–19
VTCOM.REL, 12–5
VTCOM.SAV, 12–5

W

-W-, 2–11
Warning messages, 2–11
WF:
  assigning to VM device, 11–11
Wildcards
  %, 2–30
  *, 2–30
  described, 2–30
  with backup operations, 14–8
  with restoration operations, 14–14, 14–16, 14–22
/W option
  with TRANSF.SAV, 12–17
Word (PDP–11) explained, 19–10
Working system
  for MACRO–11 programmer on VM device, 11–11
  for performing SYSGEN from VM device, 11–12
  minimal on VM device, 11–14
  on VM device, 11–4

X

XC.SYS, 12–6
XCX.SYS, 12–6
XL.SYS, 12–6
XLX.SYS, 12–6
XM monitor
  See also Mapped monitors

Z

ZM monitor
  See also Mapped monitors