Index

A

Absolute binary file format
  See .LDA files
.ABS program section
  declared in .OBJ file, 2–7
Age bits in date word, 1–9
ALL64$
  $JSX symbol, 2–35
ASCII files
  CTRL/Z with, 2–44
  described, 2–44

B

Bad block replacement
  table in home block, 1–3
Bitmap
  in .SAV files, 2–35
BUP
  saveset definition block format, 2–46
BUP magtape format, 1–32
  EOF1 label, 1–36
  EOF2 label, 1–36
  HDR1 label, 1–34
  HDR2 label, 1–35
  label and header, 1–33
  VOL1 label, 1–34
BUP volumes, 1–22
  identifier in home block, 1–22

C

CCB, 2–35
Checksum computation, 1–4
.CLOSE programmed request
  making file permanent, 1–14
Corrupted directory
  recovering from, 1–20
CREF
  chain interface, 2–45
  entry format for input file, 2–46
  file format, 2–45
CVH.DK
CVH.DK (Cont.)
  SV.CVH symbol, 2–36
CVH.ED
  SV.CVH symbol, 2–36
CVH.ID
  SV.CVH symbol, 2–36
CVH.LO
  SV.CVH symbol, 2–36
CVH.MP
  SV.CVH symbol, 2–36
CVH.XH
  SV.CVH symbol, 2–36

D

Data blocks in .OBJ module
  contents, 2–5
  ENDGSD, 2–5
  ENDMOD, 2–5
  GSD, 2–5
  ISD, 2–5
  librarian end, 2–5
  librarian header, 2–5
  RLD, 2–5
  TXT, 2–5
  types, 2–5
Date
  internal format, 1–9
Date word format, 1–9
Devices
  random access
    discussion, 1–1
    home block, 1–2
  sequential
    magtape, 1–26
  sequential-access, 1–26
Directory entry
  empty, 1–6
  format, 1–5
  permanent, 1–6
  status word format, 1–6
  status word values, 1–7
  tentative, 1–6

Directory entry status word, 1–7
Directory recovery after corruption, 1–20
Directory segment header
format, 1–5
Directory segments
calculating maximium allowed, 1–15
sample, 1–9
splitting, 1–16
why, 1–19
Directory structure
described, 1–4
disk partitioning, 1–23
format, 1–4
interchange diskette, 1–24
maximum number of possible files, 1–15
.DSK files
format of, 2–1

E

E.EOS, 1–8
E.MPTY, 1–7
E.PERM, 1–7
E.PRE, 1–7, 1–8
E.PROT, 1–8
E.READ, 1–8
E.TENT, 1–7
Empty file
defined, 1–6
ENDGSD block
end of GSD block, 2–15
.OBJ data block, 2–5
ENDMOD block
.OBJ data block, 2–5
part of .OBJ module
described, 2–26
End of module block
See ENDMOD block
.ENTER programmed request
with file creation, 1–13
EOF1 label
BUP magtapes, 1–36
file-structured magtapes, 1–32
EOF2 label
BUP magtapes, 1–36
EOV label
BUP magtapes, 1–36
ERRLOG.DAT
format, 2–48
Error Logger
Error Logger (Cont.)
buffers, 2–47
described, 2–47
file format, 2–47
EXCHANGE
used for file interchange, 1–37
Extended .SAV image
D-space header, 2–38
I-space header, 2–39

F

File formats, 2–1
ASCII or source, 2–44
CREF, 2–45
error logger, 2–47
.LDA, 2–31
library, 2–27
Logical disk files, 2–1
.OBJ, 2–2
.REL, 2–39
.SAV, 2–32
Files
empty directory entry, 1–6
finding starting block of, 1–12
maximum number possible, 1–15
permanent directory entry, 1–6
prefix block for, 1–7
protecting, 1–9
tentative directory entry, 1–6
File storage
number of files, 1–15
on a random-access device
discussion, 1–13
size of files, 1–15
Formatted binary blocks, 2–5
FRUN keyboard command
with .REL files, 2–41
with overlaid .REL files, 2–42

G

Global symbol directory block
See GSD block
GSD block
ENDGSD
end of GSD block, 2–15
entry type 0, module name, 2–8
entry type 1, control section name, 2–9
entry type 2, internal symbol name, 2–9

GSD block (Cont.)
entry type 3, transfer address, 2–9
entry type 4, global symbol name, 2–11
entry type 5, P-sect name, 2–11
flag bits, 2–13
entry type 6, program version identification, 2–13
entry type 7, mapped array declaration, 2–14
.OBJ data block, 2–5
part of .OBJ module
described, 2–7
types of entries
list, 2–7

H

HDR1 label
BUP magtapes, 1–34
HDR1 lable
file-structured magtapes, 1–31
HDR2 label
BUP magtapes, 1–35
Home block
block 1 of a random access device, 1–2
contents, 1–3

I

Interchange diskettes
directory format, 1–24
Internal symbol directory block
See ISD block
IOPAG$
$JSX symbol, 2–35
ISD block
.OBJ data block, 2–5
part of .OBJ module
described, 2–26

J

$JSW
in D-space .SAV header, 2–38
$JSX
bit definitions, 2–35
job definition word, 2–34

L

.LDA files
described, 2–31
.LDA files (Cont.)
format, 2–33
Librarian end block
.OBJ data block, 2–5
Librarian header block
.OBJ data block, 2–5
Library end block format, 2–31
Library files
format of, 2–27
directories, 2–30
header of a .MLB library, 2–29
header of a .OBJ library, 2–28
Line terminators, 2–44
formfeed, 2–44
linefeed, 2–44
RETURN, 2–44
Logical disk file format, 2–1

M

Magtapes
BUP format, 1–32
Compatible with VMS, 1–37
EOF1 label, 1–32
file structure, 1–26
HDR1 label, 1–31
implementation restrictions, 1–27
label format, 1–28
VOL1 label, 1–30
.MLB library file
directory format, 2–31
end block format, 2–31
header format, 2–29
MSCP disks
partitioning, 1–23

N

NOVBG$
$JSX symbol, 2–35

O

Object modules
combine to make a .OBJ file, 2–2
formatted binary blocks in, 2–5
.OBJ files
format of, 2–2
.OBJ library file
directory format, 2–30
end block format, 2–31

.OBJ library file (Cont.)
header format, 2–29
.OBJ module format
data blocks, 2–5
ENDGSD blocks, 2–5
ENDMOD blocks, 2–5
formatted binary blocks, 2–5
general arrangement of data blocks, 2–7
GSD blocks, 2–5
ISD blocks, 2–5
librarian end blocks, 2–5
librarian header blocks, 2–5
RLD blocks, 2–5
TXT blocks, 2–5
Overlay definition word (SV.CVH), 2–35

P

Permanent file
defined, 1–6
Prefix block, 1–7
Protecting files from deletion, 1–9

R

Random-access devices
discussion, 1–1
home block, 1–2
.REL file
block 0 format, 2–39
described, 2–39
without overlays, 2–41
with overlays, 2–42
Relocatable file format
See .REL file
Relocation directory block
See RLD block
REQID$
$JSX symbol, 2–35
REQSM$
$JSX symbol, 2–35
RLD block
entry type 1, internal relocation, 2–18
entry type 10, location counter modification, 2–21
entry type 11, program limits, 2–21
entry type 12, P-sect relocation, 2–22
entry type 13, not defined, 2–22
entry type 14, P-sect displaced relocation, 2–22
RLD block (Cont.)
entry type 15, P-sect additive relocation, 2–23
entry type 16, P-sect additive displaced, 2–23
entry type 17, complex relocation, 2–24
entry type 2, global relocation, 2–18
entry type 3, internal displaced relocation, 2–19
entry type 4, global displaced relocation, 2–19
entry type 5, global additive relocation, 2–20
entry type 6, global additive displaced, 2–20
entry type 7, location counter definition, 2–21
.OBJ data block, 2–5
part of .OBJ module
described, 2–15
types of entries
command byte, 2–17
list, 2–17

S

Save image files
See .SAV files
Saveset (BUP) format, 2–46
.SAV file
absolute block 0 of extended save image, 2–38
Extended save image format, 2–36
.SAV files
block 0 of standard image, 2–34
CCB (core control block), 2–35
described, 2–32
Relative block 0 (I-space header), 2–39
standard and extended type, 2–32
Sequential-access devices, 1–26
magtape, 1–26
Source files
See ASCII files
Splitting a directory segment
what happens, 1–16
why, 1–19
.STB file
third linker output file, 2–26
Stream ASCII file
See ASCII files

SV.CVH
bit definitions, 2–36
in .SAV image, 2–35
Symbol table definition file
See .STB file

T

Tentative file
defined, 1–6
Text file format
See ASCII files
Text information block
See TXT block
TXT block
.OBJ data block, 2–5
part of .OBJ module
described, 2–15

U

USEID$
$JSX symbol, 2–35
USESM$
$JSX symbol, 2–35

V

VBGES$
$JSX symbol, 2–36
$VIRT
in D-space .SAV header, 2–38
VMS
Magtape interchange with RT–11, 1–37
VOL1 label
BUP magtapes, 1–34
characteristics, 1–36
file-structured magtapes, 1–30